

**FFF uPVC Gravity Sewer Pipe Dimensions based on BS EN 1401 - 1 : 2009 / ISO 4435-1:2003 (Formerly BS 4660:1989 and BS 5481:1977)**

Nominal Size DN / OD	Nominal outside diameter $d_n$		SN 2		SN 8	
			SDR 41		SDR 34	
	$e_{min}$	$e_{m.max}$	$e_{min}$	$e_{m.max}$	$e_{min}$	$e_{m.max}$
110	110.0	110.3	3.2	3.8	3.2	3.8
125	125.0	125.3	3.2	3.8	3.7	4.3
160	160.0	160.4	4.0	4.6	4.7	5.4
200	200.0	200.5	4.9	5.6	5.9	6.7
250	250.0	250.5	6.2	7.1	7.3	8.3
315	315.0	315.6	7.7	8.7	9.2	10.4
400	400.0	400.7	9.8	11	11.7	13.1

# Pipe to this Specification will be supplied in 6 meters length with integral solvent weld (S/W) or Push fit (R/R)sockets

# Colour : Golden Brown

**FFF uPVC Soil and Wastage Discharge Pipe Dimensions based on BS EN 1329 - 1 : 2000 / ISO 3633-1:2002 (Formerly BS 4514:1983)**

Nominal Size DN / OD	Nominal outside diameter $d_n$		Wall thickness Application area			
			B		BD	
	$e_{min}$	$e_{m.max}$	$e_{min}$	$e_{m.max}$	$e_{min}$	$e_{m.max}$
75	75.0	75.3	3.0	3.5	3.0	3.5
110	110.0	110.3	3.2	3.8	3.2	3.8
125	125.0	125.3	3.2	3.8	3.2	3.8
160	160.0	160.4	3.2	3.8	4.0	4.6
200	200.0	200.5	3.9	4.5	4.9	5.6
250	250.0	250.5	4.9	5.6	6.2	7.1
315	315.0	315.6	6.2	7.1	7.7	8.7

# Pipe to this Specification will be supplied in 6 meters length with integral solvent weld (S/W) or Push fit (R/R)sockets, Plain end pipes of 4meters also available on request

# Colour: Light Grey